

# OPERATING PROCEDURE



**OSPREY DEEPCLEAN**  
STEAM CLEANING TECHNOLOGY

The following rules **must** be observed when using the **Steam & Vac Pro—Digital**

- **Always** Check daily before use that the power supply cable, plug and sockets are in good condition; check for visible signs of damage (do not use if damaged)
- **Always** Follow the correct procedure when filling the water reservoirs and waste tank
- **Always** Wear full PPE when working in confined spaces - mask, goggles, gloves, overalls
- **Never** allow any part of the **Steam & Vac Pro** to be immersed in water
- **Never** allow children, inexperienced, untrained or unauthorised people access to the **Steam & Vac Pro**

## Operating Procedures on the Steam & Vac Pro—Digital



Lift off removable Drum Cover



Remove Drum cover sealing element



Pour cold tap water into the waste bucket, ensure even level in both compartments



Fill up to the minimum mark



Close by inserting the sealing element



Replace drum cover housing



Unscrew the reservoir tank cap



Fill with cold tap water only



Replace the cap without tightening to much



Plug the power cable into a suitable electric socket. Press the bottom section of the on/off switch



The minimum yellow LED light will come on, after a few minutes the a green LED Light will come on. The machine is now ready for use.



Open the front panel and connect the steam hose with the red button facing upwards

## Operating Steam & Vac Pro—Continued:



Press the red steam switch on the pistol grip. By keeping the switch pressed you move through the three different steam levels, when you have reached the level required release the switch.



Press the trigger on the pistol grip to release the steam



If vacuum is required press the white vacuum switch on the pistol grip. By keeping the switch pressed you move through the three different vacuum levels. When you have reached the vacuum level required, release the white vacuum switch.



Note: If not used for 5 minutes. Switch on/off switch on to reset steam switch.

## Emptying the Waste Bucket:

The waste bucket must be emptied upon hearing the audible alarm & vacuum cut off. Switch off & disconnect from mains.



Lift of removable drum cover



Remove Drum cover sealing element



Empty waste bucket & clean thoroughly



Close by inserting the sealing element



Replace drum cover housing